














## TAPISOM 600

Made in EEC

Factory ISO 9001 Quality Management System  
 Factory ISO 14 001 Environmental Management System  
 Factory OHSAS 18001 Health, Safety and Security Management System

SPECIFICATIONS						Article n° : 416002009 00XXX	
DESCRIPTION	NORM	DATA		20 colors	Reflectance Index (%)		
Type de revêtement / Type of flooring		Aiguilleté plat / Flat needle felt		(2671) / 004			
Type d'enduction / Type of bonding		Enduction d'envers / Back coated		(2676) / 009			
Composition de la couche de surface / Fibre composition of use surface		100% Polyamide		(2677) / 010			
Poids total du velours / Total fibre weight of use surface	ISO 8543	430 g/m <sup>2</sup>		(2678) / 011			
Epaisseur totale / Total Thickness	ISO 1765	4.4 mm		(9833) / 013			
Masse totale / Total Weight	ISO 8543	950 g/m <sup>2</sup>		(9837) / 014			
Envers / Backing		100% Synthetic		(9842) / 015	19,5%		
Dimensions / Size		200cm lés (Rolls: 40 lm)		(9843) / 016			
Sens de pose / Installation		↑↑		(9882) / 019			
				(9889) / 021	21,9%		
TECHNICAL PERFORMANCES						(9969) / 023	
Classification (EN 1470)	Class:		23/32 - Commercial General		(9971) / 025		
			LC1		026		
				027			
Classement UPEC (Référentiel NF 262)	Classement:		U3P3E1C0		028		
	Certificat n°:		349TA-001.1		029		
				030			
 Fire rating	EN 13501-1		 Impact noise reduction	ISO 717/2	ΔL <sub>(w)</sub> 18 dB		031
	BfS1		 Sound absorption	ISO 11654	α <sub>w</sub> = 0,15 (H)		032
 Electrostatic properties	ISO 6356	≤ 2,0kV	 Colour Fastness	EN 105 - B02	≥6/8		033
			 Castor Chair	EN 985	Passed R <sub>≥2,4</sub>		
	ISO 10965	≤ 10 <sup>8</sup> Ω	 Heated Floor	EN 12524	0,07 m <sup>2</sup> K/W		
 Suitability for use on stairs	EN 1963			CE 07			
	YES			EN 14041: 2004 Reaction to fire classification Test n° RA07-0117			
ENVIRONMENTAL ISSUES							
 ÉMISSIONS DANS L'AIR INTÉRIEUR		 <b>A+</b>		<b>HQE</b> : Ce produit participe à 9 des cibles nécessaires à l'obtention de la certification HQE d'un bâtiment. Se reporter à la FDES suivant NF P01-010 pour l'ACV.		<b>LEED</b> : This product contributes to obtain points towards MR2, MR4, MR5, IEQ4.1 and IEQ4.3 credits to the LEED certification of your buildings.	
The above information is subject to modifications for the benefit of further improvement. Updated on 01/12/2012							